Payanywhere Core Specifications

payanywhere







Software	The Payanywhere Application
Operating System	Android 13
Processor	Octa-core, up to 2.4GHz
Memory	4GB RAM + 64GB ROM | Extended Micro SD Card Slot Up to 512GB
Card Readers	Chip | NFC Contactless | Magstripe | PIN
Camera	5MP Front-Facing Camera | 13MP Rear-Facing Camera
Display	11” WUXGA, 1920x1200 pixels, IPS Capacitive Multi-touch Screen
Comms Configurations	4G and Wi-Fi 5GHz/2.4GHz + Bluetooth
Battery	8000 mAh | 3.87 V
Printer	Printing Method: Thermal | Paper width: 80mm | Effective Print Width: 72mm | Print speed: 250mm/s Cutter Life: >1.5 Million times | Bluetooth and Ethernet Connectivity
Keys / Buttons	1*Power button (Fingerprint ID) | 1*Volume button
Audio	1 Speaker | 2 Microphones
Ports	Tablet: 1*Type-C on the left, USB OTG | 1*Type-C at the bottom, USB host only | 1*Kensington Printer: Cash Drawer RJ12 | Type-C USB 2.0 | LAN Ethernet RJ45 Base: Power Port USB Type-A | Accessory Ports 2 USB Type-C
Adapter	Input: 100-240V AC | Output: 9V2A DC
Physical	Tablet: 265.6 x 177.25 x 10.95 mm | 606g (including battery) Printer: 130 x 130 x 130 mm | 855g (without paper)
Environmental	Operating temperature: -10°C~50°C | Storage temperature: -20°C~70°C | Operating Humidity: 5%~95% non-condensing
Certifications	PCI PTS 6.x, EMV L1 & L2, EMV Contactless L1, Visa payWave, MasterCard PayPass, UPI Quickpass, Amex ExpressPay, Discover D-PAS, JCB, TQM, FCC, ISED, CE, CB, RoHS, WEEE, REACH

Name | Email | Phone | Website

©2026 Payanywhere. All rights reserved. Payanywhere is a registered DBA of EPX, a registered ISO of BMO Bank N.A., Chicago, IL, Citizens Bank N.A., Providence, RI, The Bancorp Bank, Philadelphia, PA, FFB Bank, Fresno, CA., and a registered ISO/MSP of Merrick Bank, South Jordan, UT.